

The ROBORIGGER AR10 and AR15 provide the full Roberigger functionality:

- Improving safety by allowing loads to be controlled easily by remote control with the dogman located away from the load and the crane
- Make lifting operations easier and quicker and eliminating the need for tag lines
- Increase operational efficiency by logging all load movements with images and weight

The AR10 and AR15 are designed to lift loads up to 10/15t WLL and to control a load the size of a 6m ISO container in winds up to 27km/hr gusting to 35km/hr. Loads with less windage can be controlled in higher wind speeds.

Each unit comes with the ability to use 2 remote controls to allow handover between 2 dogmen.

Roberiggers are designed for an ultimate capacity of 5xWLL and are load tested to 2xWLL.

	<b>KEY FEATURES:</b>
	<ul style="list-style-type: none"><li>• Robust and reliable design.</li><li>• Wireless remote control with 100m min range.</li><li>• Load cell with remote readout</li><li>• Camera that takes snapshots of all lifts and setdowns as well as providing video feed to crane operator</li><li>• Battery operated with capability to last at least 12 hours</li><li>• Minimal operator training required.</li><li>• Optional remote release of hooks with failsafe protection.</li><li>• Online monitoring and diagnosis</li><li>• Full charge in 8-10 hours.</li></ul>
	<b>SPECIFICATIONS:</b>
	<p><b>WLL:</b> 10t and 15t <b>Size:</b> 1.4m (diam) x 1.8m(H) <b>Weight:</b> 700kg (AR10) 850kg (AR15)</p>
	<p>Online monitoring of all lifts and Roberigger performance and productivity</p>